



Reviewed on 04/02/2015

1 Identification

- · Product identifier
- · Trade name: 39643 TAC-Free Aerosol
- Article number: 39643
- **Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Coating

Details of the supplier of the safety data sheet
Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

• Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture

 $\langle \mathfrak{B} \rangle$

GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

GHS08 Health hazard		
Repr. 2	H361	Suspected of damaging fertility or the unborn child.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.

GHS07

	Skin Irrit. 2	H315	Causes skin irritation.
	Eye Irrit. 2A	H319	Causes serious eye irritation.
	STOT SE 3	H336	May cause drowsiness or dizziness.
1			

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

(Contd. on page 2)

USA

Printing date 04/02/2015

Reviewed on 04/02/2015

SEM

Trade name: 39643 TAC-Free Aerosol

Hazard-determining components of labeling: toluene cacetone buttanone benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate Hazard statements W1222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated. H315 Causes skin irritation. H319 Causes serious eye irritation. H333 May cause damagite of grants. H333 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. Precationary statements P200 P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P303+P310 If swallowed: Immediately call a poison center/doctor. P304 Bay to do. Continue rinsing. P321 Specific treatment (see on this label). P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/internationaregulations. classification systement Nep Equations.		(Contd. of page 1)
acetone butanone benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate Hazar statements H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated. H315 Causes skin irritation. H319 Causes serious eye irritation. H319 Causes serious eye irritation. H336 May cause drawsiness or dizziness. H337 May cause damaging jerility or the unborn child. H336 May cause damaging jerility or the unborn child. H337 May cause damaging jerility or the unborn child. H338 May cause damaging jerility or the unborn child. H339 May be fatal if swallowed and enters airways. Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P260 Do not breathe dustfiume/gas/mist/vapors/spray. P301+P310 If swallowed: Immediately call a poison center/actor. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if presen and easy to do. Continue rinsing. P321 Specific treatment (see on this label). P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/internationar regulations. Classification system: NFPA ratings (scale 0 - 4) Fire = 4 Reactivity = 3 HMIS-ratings (scale 0 - 4) Reactivity = 3 HMIS-ratings (scale 0 - 4) Reactivity = 3 HMIS-ratings (scale 0 - 4) Reactivity = 4 Reactivity = 4 Reactivity = 5 HMIS-ratings (scale 0 - 4) Reactivity = 4 Reactivity = 4 Reactivity = 5 HMIS-ratings (scale 0 - 4) HMIS-ratings (scale 0 - 4	· Hazard-a	letermining components of labeling:
butanone berezyl 3-isoburyloxy-1-isopropyl-2-2-dimethylpropyl phhalate Hazard statements H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated. H315 Causes skin irritation. H316 Suspected of damaging fertility or the unborn child. H336 May cause dorwsiness or dizziness. H337 May cause dorwsiness or dizziness. H337 May cause damage to organs through prolonged or repeated exposure. H344 May be fatal if swallowed and enters airways. Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P260 Do not breathe dust/fume/gas/mist/vapors/spray. P301+P310 If swallowed: Immediately call a poisson center/doctor. P305+P351+P388 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if presen and easy to do. Continue rinsing. P301 Specific treatment (see on this label). P405 Store locked up. P409 P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. Classification system: NFPA ratings (scale 0 - 4) H4L11 If Health = 1 Fire = 4 Reactivity = 3 HMIS-ratings (scale 0 - 4) H4L11 If Health = *1 Health = 1 Fire = 4 Reactivity = 3 HMIS-ratings (scale 0 - 4) H4L11 If Health = *1 Health = *1 Hea	toluene	
benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate Hazard statements Haz2-H222-H222 Extremely flammable aerosol. Pressurized container: May burst if heated. H315 Causes skin irritation. H319 Causes serious eye irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or diziness. H337 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P260 Do not breath dust/fume/gas/mist/vapors/spray. P301+P310 If swallowed: Immediately call a poison center/doctor. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if presen and easy to do. Continue rinsing. P321 Specific treatment (see on this label). P405 Store locked up. P410+P412 Protect from sullight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/internationar regulations. Classification system: NFPA ratings (scale 0 - 4) Halth = 1 Fire = 4 Reactivity = 3 HMIS-ratings (scale 0 - 4) HALTH 1 Health = 1 Fire = 4 Reactivity = 3 HMIS-ratings (scale 0 - 4) HALTH 1 Health = 1 Fire = 4 Reactivity = 3 Other hazards Results of PBT and vPvB assessment PBT: vinyl resin +PoB: Not applicable.	acetone	
Harad statementsHarthH222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.H315Causes skin irritation.H316Suspected of damaging fertility or the unborn child.H337May cause drowsiness or dizziness.H336May cause damage to organs through prolonged or repeated exposure.H347May cause damage to organs through prolonged or repeated exposure.H348May cause damage to organs through prolonged or repeated exposure.H349May cause damage to organs through prolonged or repeated exposure.H344May be fatal if swallowed and enters airways.Precautionary statementsP210Keep away from heat/sparks/open flames/hot surfaces No smoking.P251Pressurized container: Do not pierce or burn, even after use.P305+P351+P338 [f in eyes: Rins cautiously with water for several minutes. Remove contact lenses, if presen and easy to do. Continue rinsing.P321Specific treatment (see on this label).P405Store locked up.P410+P412Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.P501Dispose of contents/container in accordance with local/regional/national/internationa regulations.• NFPA ratings (scale 0 - 4)Health = 1 Fire = 4 Reactivity = 3• HMIS-ratings (scale 0 - 4)Health = *1 Fire = 4 Reactivity = 3• Other hazards Results of PBT and vPvB assessment• PBT: vinyl resin• PvB: Not applicable.• VPvB: Not applicable.	butanone	
H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated. H315 Causes serious eye irritation. H316 Causes serious eye irritation. H316 Suspected of damaging fertility or the unborn child. H336 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P211 Pressurized container: Do not pierce or burn, even after use. P220 Do not breath dust/flum/gas/mayray. P301+P310 If swallowed: Immediately call a poison center/doctor. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if presen and easy to do. Continue rinsing. P321 Specific treatment (see on this label). P405 Store locked up. P410+P412 Protect from sulight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. Classification system: NFPA ratings (scale 0 - 4) H41h = 1 Fire = 4 Reactivity = 3 HMIS-ratings (scale 0 - 4) H421H 1 Health = *1 Fire = 4 Reactivity = 3 HMIS of PBT and vPvB assessment - PBT: vinyl resin - vPvB: Not applicable. B Composition/information on ingredients	benzyl 3-	isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
 H315 Causes skin irritation. H319 Causes serious eye irritation. H361 Suspected of damaging fertility or the unborn child. H336 May cause drowsiness or dizziness. H373 May cause drowsiness or dizziness. H374 May be fatal if swallowed and enters airways. Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P260 Do not breathe dust/fume/gas/mist/sapors/spray. P301+P310 If swallowed: Immediately call a poison center/doctor. P305+P351+P338 If in eyes: Rine cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P321 Specific treatment (see on this label). P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. Classification system: NFPA ratings (scale 0 - 4) Health = 1 Fire = 4 Reactivity = 3 HMIS-ratings (scale 0 - 4) Health = 1 Fire = 4 Reactivity = 3 Other hazards Results of PBT and vPvB assessment • PBT: vinyl resin • PvB: Not applicable. 	-	
H319 Causes serious eye irritation. H3161 Suspected of damaging fertility or the unborn child. H336 May cause damage to organs through prolonged or repeated exposure. H337 May cause damage to organs through prolonged or repeated exposure. H344 May be fatal if swallowed and enters airways. Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P260 Do not breathe dus/fume/gas/misi/vapors/spray. P301+P310 If swallowed: Immediately call a poison center/doctor. P305 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/internationaregulations. • Classification system: • NFPA ratings (scale 0 - 4) ● 1 ● 1 ● 1 ● 1 ● 1 ● 1 ● 1 ● 1 ● 1 ● 1 ● 1 ● 1 ● 1 ● 1 ● 2 ● 1 ● 1 ● 1	H222-H2	29 Extremely flammable aerosol. Pressurized container: May burst if heated.
H361 Suspected of damaging fertility or the unborn child. H351 May cause drowsiness or dizziness. H373 May cause drowsiness or dizziness. H374 May be fatal if swallowed and enters airways. Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P260 Do not breathe dust/fume/gas/mist/vapors/spray. P301+P310 If swallowed: Inmediately call a poison center/doctor. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P321 Specific treatment (see on this label). P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. Classification system: NFPA ratings (scale 0 - 4) Health = 1 Fire = 4 Reactivity = 3 HMIS-ratings (scale 0 - 4) Health = 1 Fire = 4 Reactivity = 3 HMIS-ratings (scale 0 - 4) Health = 1 Fire = 4 Reactivity = 3 Other hazards Results of PBT and vPvB assessment P40 P40 P40 P40 P40 P40 P40 P40		Causes skin irritation.
H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H374 May be fatal if swallowed and enters airways. Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P260 Do not breathe dust/fume/gas/mist/vapors/spray. P301+P310 If swallowed: Immediately call a poison center/doctor. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if presen and easy to do. Continue rinsing. P321 Specific treatment (see on this label). P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. • Classification system: • NFPA ratings (scale 0 - 4) HEALTH I Health = 1 Fire = 4 Fire = 4 Reactivity = 3 • Other hazards • Results of PBT and vPvB assessment • vPvB: Not applicable. • Composition/information on ingredients	H319	
H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P260 Do not breathe dust/fume/gas/mist/vapors/spray. P301+P310 If swallowed: Immediately call a poison center/doctor. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P321 Specific treatment (see on this label). P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. • Classification system: • NFPA ratings (scale 0 - 4) Health = 1 Fire = 4 Reactivity = 3 • Uther hazards • Results of PBT and vPvB assessment • PB: Not applicable. • Composition/information on ingredients		
 H304 May be fatal if swallowed and enters airways. Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P260 Do not breathe dust/jume/gas/mist/vapors/spray. P301+P310 If swallowed: Immediately call a poison center/doctor. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P321 Specific treatment (see on this label). P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/internationa regulations. Classification system: NFPA ratings (scale 0 - 4) Health = 1 Fire = 4 Reactivity = 3 HMIS-ratings (scale 0 - 4) HEALTH I Health = *1 Fire = 4 Fire =	H336	
Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P260 Do not breathe dust/fume/gas/mist/vapors/spray. P301+P310 If swallowed: Immediately call a poison center/doctor. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P321 Specific treatment (see on this label). P400-P412 Protect from sulight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. Classification system: . NFFA ratings (scale 0 - 4) . Image: Specific treat = 4 . Reactivity = 3 . HMIS-ratings (scale 0 - 4) . Image: Specific treat . P400+ . Image: Specific treatment (see on this label). . NFFA ratings (scale 0 - 4) . Image: Specific treatment (see on this label). . NFFA ratings (scale 0 - 4) . Image: Specific treatment (see on this label). . <tr< td=""><td>H373</td><td></td></tr<>	H373	
P210Keep away from heat/sparks/open flames/hot surfaces No smoking.P251Pressurized container: Do not pierce or burn, even after use.P260Do not breathe dust/fume/gas/mist/vapors/spray.P301+P310If swallowed: Immediately call a poison center/doctor.P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.P321Specific treatment (see on this label).P405Store locked up.P410+P412Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.P501Dispose of contents/container in accordance with local/regional/national/international regulations.• Classification system:•• NFPA ratings (scale 0 - 4)Image: the start of the sta	H304	May be fatal if swallowed and enters airways.
P251Pressurized container: Do not pierce or burn, even after use.P260Do not breathe dust/fume/gas/mist/vapors/spray.P301+P310If swallowed: Immediately call a poison center/doctor.P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.P321Specific treatment (see on this label).P405Store locked up.P410+P412Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.P501Dispose of contents/container in accordance with local/regional/national/international regulations.• Classification system:• NFPA ratings (scale 0 - 4)HEALTHI Fire = 4 Reactivity = 3• HMIS-ratings (scale 0 - 4)HEALTHI Health = 1 Fire = 4 Reactivity = 3• Other hazards Results of PBT and vPvB assessment• PFN: vinyl resin• vPvB: Not applicable.	· Precautio	onary statements
P260Do not breathe dust/fume/gas/mist/vapors/spray.P301+P310If swallowed: Immediately call a poison center/doctor.P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.P321Specific treatment (see on this label).P405Store locked up.P410+P412Protect from sulight. Do not expose to temperatures exceeding 50 °C/122 °F.P501Dispose of contents/container in accordance with local/regional/national/international regulations.• Classification system:•• NFPA ratings (scale 0 - 4)Image: the start of th		
 P301+P310 If swallowed: Immediately call a poison center/doctor. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if presen and easy to do. Continue rinsing. P321 Specific treatment (see on this label). P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/internationa regulations. Classification system: NFPA ratings (scale 0 - 4) Health = 1 Fire = 4 Reactivity = 3 HMIS-ratings (scale 0 - 4) Health = *1 Fire = 4 Reactivity = 3 Other hazards Results of PBT and vPvB assessment • PBT: vinyl resin Organization on ingredients 	P251	Pressurized container: Do not pierce or burn, even after use.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P321 Specific treatment (see on this label). P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. Classification system: • NFPA ratings (scale 0 - 4) Health = 1 Fire = 4 Reactivity = 3 • HMIS-ratings (scale 0 - 4) HEALTH 1 Health = *1 Fire = 4 Reactivity 3 • Other hazards • Results of PBT and vPvB assessment • vPvB: Not applicable. B Composition/information on ingredients	P260	Do not breathe dust/fume/gas/mist/vapors/spray.
and easy to do. Continue rinsing. P321 Specific treatment (see on this label). P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. • Classification system: • NFPA ratings (scale 0 - 4)		
 P321 Specific treatment (see on this label). P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. • Classification system: • NFPA ratings (scale 0 - 4) 	P305+P3	351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
P405Store locked up.P410+P412Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.P501Dispose of contents/container in accordance with local/regional/national/international regulations.• Classification system:.• NFPA ratings (scale 0 - 4).Image: transformation of t		and easy to do. Continue rinsing.
P410+P412Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local/regional/national/international regulations.• Classification system: • NFPA ratings (scale 0 - 4)•• 1^{4} •• Health = 1 Fire = 4 Reactivity = 3• HMIS-ratings (scale 0 - 4)• HEALTH • Fire = 4 Reactivity = 3• Other hazards • Results of PBT and vPvB assessment• PBT: vinyl resin • vPvB: Not applicable.• Composition/information on ingredients	P321	Specific treatment (see on this label).
P501Dispose of contents/container in accordance with local/regional/national/international regulations.• Classification system: • NFPA ratings (scale $0 - 4$)• Health = 1 Fire = 4 Reactivity = 3• HMIS-ratings (scale $0 - 4$)• HEALTH • TRE • Reactivity = 3• Other hazards • Results of PBT and vPvB assessment• PBT: vinyl resin • vPvB: Not applicable.• Composition/information on ingredients	P405	Store locked up.
regulations. • Classification system: • NFPA ratings (scale 0 - 4)	P410+P4	412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 NFPA ratings (scale 0 - 4) Health = 1 Fire = 4 Reactivity = 3 HMIS-ratings (scale 0 - 4) HEALTH 1 HEALTH 1 FIRE 4 REACTIVITY 3 Reactivity = 3 Other hazards Results of PBT and vPvB assessment PBT: vinyl resin vPvB: Not applicable. 	P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Fire = 4 Reactivity = 3 HMIS-ratings (scale 0 - 4) HEALTH [1] HEALTH [1] Health = *1 Fire = 4 Reactivity] Reactivity = 3 Other hazards Results of PBT and vPvB assessment PBT: vinyl resin vvPvB: Not applicable.		
Image: Composition/information on ingredients		Health = 1
 HMIS-ratings (scale 0 - 4) HEALTH Health = *1 FIRE Fire = 4 REACTIVITY BReactivity = 3 Other hazards Results of PBT and vPvB assessment PBT: vinyl resin vPvB: Not applicable. 	4	
HEALTH I FIRE I Fire 4 Fire 4 REACTIVITY 3 Participation PBT and vPvB assessment • PBT: vinyl resin • vPvB: Not applicable. S B Composition/information on ingredients		3 Reactivity = 3
FIRE 4 Fire = 4 REACTIVITY 3 Cother hazards • Other hazards • Results of PBT and vPvB assessment • PBT: vinyl resin • vPvB: Not applicable. B Composition/information on ingredients	· HMIS-ra	tings (scale 0 - 4)
REACTIVITY 3 Reactivity = 3 • Other hazards . • Results of PBT and vPvB assessment . • PBT: . vinyl resin . • vPvB: Not applicable. . B Composition/information on ingredients	HEALTH	*1 $Health = *1$
 Other hazards Results of PBT and vPvB assessment PBT: vinyl resin vPvB: Not applicable. B Composition/information on ingredients 	FIRE	4 $Fire = 4$
 Other hazards Results of PBT and vPvB assessment PBT: vinyl resin vPvB: Not applicable. B Composition/information on ingredients 	REACTIVI	TY [3] Reactivity = 3
 Results of PBT and vPvB assessment PBT: vinyl resin vPvB: Not applicable. B Composition/information on ingredients		
• PBT: vinyl resin • vPvB: Not applicable. B Composition/information on ingredients		-
vinyl resin • vPvB: Not applicable. B Composition/information on ingredients	· Results o	f PBT and vPvB assessment
• vPvB: Not applicable. B Composition/information on ingredients	· PBT:	
• vPvB: Not applicable. B Composition/information on ingredients	vinyl resi	n
	-	
	3 Compos	sition/information on ingredients
· Chemical characterization: Mixtures	- compo	
	· Chemica	l characterization: Mixtures

· Description:

*

Mixture: consisting of the following components. Weight percentages

 $(Contd. \ on \ page \ 3)$

USA



Reviewed on 04/02/2015

Trade name: 39643 TAC-Free Aerosol

		(Contd. of page 2)
· Dangerous	components:	
115-10-6	dimethyl ether	13 - 30%
67-64-1	acetone	13 - 30%
108-88-3	toluene	13 - 30%
78-93-3	butanone	13 - 30%
2807-30-9	2-(propyloxy)ethanol	1.5 - 5%
108-65-6	2-methoxy-1-methylethyl acetate	1.5 - 5%
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate	1.5 - 5%
	vinyl resin	1.5 - 5%

*

4 First-aid measures

- · Description of first aid measures
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- *Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.*
- Do not flush with water or aqueous cleansing agents
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

US/

Printing date 04/02/2015

Reviewed on 04/02/2015

Trade name: 39643 TAC-Free Aerosol

(Contd. of page 3)

7 Handling and storage

· Handling:

• **Precautions for safe handling** No special measures required. Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

• Information about protection against explosions and fires: Do not spray on a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:
- Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- Information about storage in one common storage facility: Store away from oxidizing agents.
- \cdot Further information about storage conditions:
- Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

- Protect from heat and direct sunlight.
- \cdot Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

•	Control	parameters
---	---------	------------

115-10	0-6 dimethyl ether
WEEL	Long-term value: 1000 ppm
67-64-	1 acetone
PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m³, 250 ppm
TLV	Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm BEI
108-88	8-3 toluene
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm
TLV	Long-term value: 75 mg/m³, 20 ppm BEI

Printing date 04/02/2015

SEM Reviewed on 04/02/2015

Trade name: 39643 TAC-Free Aerosol

78-93-	3 butanone (Contd. of page
PEL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm
KLL	Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm
1 L V	Long-term value: 590 mg/m ³ , 200 ppm
	BEI
108-65	-6 2-methoxy-1-methylethyl acetate
WEEL	Long-term value: 50 ppm
· Ingred	ients with biological limit values:
67-64-1	1 acetone
BEI 50	
	edium: urine
	me: end of shift
	arameter: Acetone (nonspecific)
	-3 toluene
	02 mg/L
	edium: blood
	me: prior to last shift of workweek
P	arameter: Toluene
0	03 mg/L
	edium: urine
	ime: end of shift
	arameter: Toluene
	3 mg/g creatinine
	edium: urine
	me: end of shift
	arameter: o-Cresol with hydrolysis (background)
78-93-3	3 butanone
BEI 2	
	edium: urine
	me: end of shift
	arameter: MEK
· Additio	nal information: The lists that were valid during the creation were used as basis.
Exposi	<i>ure controls</i>
	al protective equipment:
· Genera	Il protective and hygienic measures:
	way from foodstuffs, beverages and feed.
	iately remove all soiled and contaminated clothing.
	ands before breaks and at the end of work.
	contact with the eyes and skin.
	ing equipment:
	of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure us tory protective device that is independent of circulating air
respira	tory protective device that is independent of circulating air.

Page 5/12

Printing date 04/02/2015

SEM

(Contd. of page 5)

Reviewed on 04/02/2015

Trade name: 39643 TAC-Free Aerosol

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material


The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Aerosol Color: According to product specification · Odor: **Characteristic** · Odour threshold: Not determined. · pH-value: Not determined. · Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: -24 °C · Flash point: -42 °C Not applicable. · Flammability (solid, gaseous): 235 °C · Ignition temperature: · Decomposition temperature: Not determined. · Auto igniting: Product is not selfigniting. · Danger of explosion: In use, may form flammable/explosive vapour-air mixture. · Explosion limits: 1.2 Vol % Lower: Upper: 18.6 Vol % (Contd. on page 7) USA



Reviewed on 04/02/2015

Trade name: 39643 TAC-Free Aerosol

		(Contd. of page 6
• Vapor pressure at 20 •C:	5200 hPa	
Density at 20 °C:	0.8143 g/cm ³	
Relative density	Not determined.	
· Vapour density	Not determined.	
• Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/	water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	93.2 %	
VOC content:	69.1 %	
	748.8 g/l / 6.25 lb/gl	
Solids content:	6.9 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:
- Nitrogen oxides
- Hydrocarbons

Carbon monoxide and carbon dioxide

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 8)

USA

Printing date 04/02/2015

Reviewed on 04/02/2015

(Contd. of page 7)

Trade name: 39643 TAC-Free Aerosol

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
108-88-3	toluene	3
	BENTONITE	suspected carcinogen <2% 14808-60-7
· NTP (National Toxicology Program)		
None of th	ne ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)		

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

· PBT:

vinyl resin

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN1950	
· UN proper shipping name		
$\cdot DOT$	Aerosols, flammable	



Reviewed on 04/02/2015

SEM

Trade name: 39643 TAC-Free Aerosol

		(Contd. of page
· ADR	1950 Aerosols	
·IMDG	AEROSOLS	
· IATA	AEROSOLS, flammable	
• Transport hazard class(es)		
·DOT		
()		
· Class · Label	2.1 2.1	
· ADR		
()		
· Class	2 5F Gases	
· Label	2.1	
*		
· Class · Label	2.1 2.1	
· Packing group · DOT, ADR, IMDG, IATA	Void	
· Environmental hazards:		
• Marine pollutant:	No	
· Special precautions for user	Warning: Gases	
· EMS Number:	F-D,S-U	
• Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.	
· Transport/Additional information:		
·DOT		
• Quantity limitations	On passenger aircraft/rail: 75 kg	
	On cargo aircraft only: 150 kg	
· Remarks	ORM-D 49CFR 173.150,156,306	
ADR		
\cdot Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity	
MDC		
· IMDG · Limited quantities (LQ)	IL	
		(Contd. on page



Page 10/12

(Contd. of page 9)

Reviewed on 04/02/2015

Printing date 04/02/2015

Trade name: 39643 TAC-Free Aerosol

 \cdot Excepted quantities (EQ)

Code: E0 Not permitted as Excepted Quantity

UN1950, Aerosols, 2.1

· UN "Model Regulation":

*

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

	extremely hazardous substances):
None of the in	ngredient is listed.
· Section 313 (Specific toxic chemical listings):
108-88-3 tol	uene
78-93-3 but	tanone
71-36-3 but	tan-1-ol
· TSCA (Toxic	Substances Control Act):
115-10-6	dimethyl ether
67-64-1	acetone
108-88-3	toluene
78-93-3	butanone
2807-30-9	2-(propyloxy)ethanol
108-65-6	2-methoxy-1-methylethyl acetate
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
	vinyl resin
71-36-3	butan-1-ol
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate
104810-48-2	alpha-3-(3-(2H-Benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega hydroxypoly(oxy-ethylen)
104810-47-1	alpha-3-(2H-Benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl)-omega-3-(3-(2H-benzo triazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylen)
82919-37-7	Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate
25322-68-3	Polyethylene glycol
106-79-6	Dimethyl sebacate(Impurity)
· Proposition 6	55
· Chemicals kr	nown to cause cancer:
None of the in	ngredients is listed.
· Chemicals kr	nown to cause reproductive toxicity for females:
108-88-3 tol	uene
· Chemicals kr	nown to cause reproductive toxicity for males:
	ngredients is listed.
· Chemicals kr	nown to cause developmental toxicity:
108-88-3 tol	
	(Contd. on page 2



Page 11/12

Reviewed on 04/02/2015

Printing date 04/02/2015


Trade name: 39643 TAC-Free Aerosol

(Contd.	of page	10)

· Cancerogenity categories	ontal of page 10)
· EPA (Environmental Protection Agency)	
67-64-1 acetone	I
108-88-3 toluene	II
78-93-3 butanone	I
71-36-3 butan-1-ol	D
· TLV (Threshold Limit Value established by ACGIH)	
67-64-1 acetone	A4
108-88-3 toluene	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
• GHS label elements The product is classified and labeled according to the Globally Harmonized Sys • Hazard pictograms	tem (GHS).
GHS02 GHS04 GHS07 GHS08	
· Signal word Danger	

Hazard-determ	nining components of labeling:
toluene	
acetone	
butanone	
benzyl 3-isobu	tryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
Hazard statem	
	xtremely flammable aerosol. Pressurized container: May burst if heated.
H315 C	auses skin irritation.
H319 C	auses serious eye irritation.
H361 Sı	ispected of damaging fertility or the unborn child.
Н336 М	ay cause drowsiness or dizziness.
Н373 М	ay cause damage to organs through prolonged or repeated exposure.
	ay be fatal if swallowed and enters airways.
Precautionary	statements
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P251	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P305+P351+	P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 $^{\circ}C/122$ $^{\circ}F$.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Chemical safe	ty assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 12)





Page 12/12

Reviewed on 04/02/2015

Trade name: 39643 TAC-Free Aerosol

(Contd. of page 11)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- Contact: Steve Gaver (sgaver@semproducts.com)
- · Date of preparation / last revision 04/02/2015 / 4

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Flam. Aerosol 1: Flammable aerosols, Hazard Category 1 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A Repr. 2: Reproductive toxicity, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Asp. Tox. 1: Aspiration hazard, Hazard Category 1 \cdot * Data compared to the previous version altered.