

# REX TEX APPLICATIONS

- Covers • Truck Tarpaulins • Container Booms
- Marine Hatch Covers • Pole Vault Pits & Jump Pits


**Rex Pegg Fabrics** offers welding service on **Rex-TEX Vinyl** for your convenience.

- Truck tarps, hay tarps, pool covers • Almost any size you need
- Call for quotes on our quick and reliable welding service

| <b>REX TEX SPECIFICATIONS</b> |                                |               |                           |
|-------------------------------|--------------------------------|---------------|---------------------------|
|                               | <b>Test Method<br/>FS191 A</b> | <b>Unit</b>   | <b>Results</b>            |
| Yarn                          |                                |               | Polyester 1,000D X 1,300D |
| Fabric Density                |                                | / sq. inch    | 18 x 17                   |
| Total Weight                  |                                | oz. / sq. yd. | 18.5                      |
| Cut Strip Tensile             | 5102                           | lbs. / inch   | 300 x 300                 |
| Single Rip Tongue Tear        | 5134                           | lbs.          | 100 x 100                 |
| Abrasion                      | 5970                           | lbs. / inch   | 12 x 10                   |
| Cold Crack                    | 5874                           | °F            | -40°                      |
| Standard Width                |                                |               | 61"                       |
| Put Up                        |                                |               | 100 yards                 |

**10 oz Banner White** vinyl laminated polyester for One-Sided printing. Exceptionally smooth print side suitable for Screen Printing, Digital Printing and Banner/Signs. Excellent Lay-Flat characteristics.

| <b>10 oz BANNER WHITE SPECIFICATIONS</b> |                                |               |                       |
|--|--------------------------------|---------------|-----------------------|
|  | <b>Test Method<br/>FS191 A</b> | <b>Unit</b>   | <b>Results</b>        |
| Yarn                                     |                                |               | Polyester 250D X 500D |
| Fabric Density                           |                                | / sq. inch    | 18 x 12               |
| Total Weight                             |                                | oz. / sq. yd. | 10                    |
| Cut Strip Tensile                        | 5102                           | lbs. / inch   | 145 x 126             |
| Single Rip Tongue Tear                   | 5134                           | lbs.          | 41 x 36               |
| Abrasion                                 | 5970                           | lbs. / inch   | 10 x 2                |
| Hydrostatic Resistance                   | 5512                           | PSI           | 170 PSI               |
| Cold Crack                               | 5874                           | °F            | -10°                  |
| Flame Resistance                         |                                |               | Yes                   |
| Standard Width                           |                                |               | 63"                   |
| Put Up                                   |                                |               | 100 yards             |



**REX PEGG**  
fabrics, inc.

1802 East Stewart Street  
Tacoma, Washington 98421  
(253) 272-5162  
Fax (253) 591-7059