



Corinthian

Product Specifications:

General

Total Wt. - oz./sq. yd. (CFFA-700d)	20 ± 10%
Total Wt. - oz./lin. yd. (CFFA-700d)	30
Width (min.) - in. (CFFA-700a)	54"
Face Content	PVC

Backing

Construction	Terry Knit
Weight - oz./sq. yd.	3.7
Content	Polyester
Fiber Type	Filament

Adhesion (CFFA-3)

Pounds/Inches (min.)	Warp 4 Fill 4
----------------------	------------------

Tensile Strength (CFFA-17)

Pounds (min.)	Warp 85 Fill 75
---------------	--------------------

Trap Tear Strength (CFFA-16c)

Pounds (min.)	Warp 20 Fill 27
---------------	--------------------

Tack Strength (Stitch) (CFFA-14)

Pounds (min.)	Warp 35 Fill 30
---------------	--------------------

Performance Testing: meets or exceeds

Abrasion (CFFA-1a)

Wyzenbeek, Wire Screen	6,000 cycles
Wyzenbeek, Cotton Duck	10,000 cycles

Blocking (CFFA-4)

No. 2 max

W-Flex (CFFA-10)

25,000 cycles

Crock (CFFA-7)

20 cycles - no stain

UV (CFFA-2)

QUV	650 hours
-----	-----------

Cold Crack (CFFA-6a)

Roller Temperature	-20°F
--------------------	-------

Flame Retardancy

FMVSS-302	Pass
California Tech. Bulletin 117	Pass
BIFMA	Pass
UFAC Fabric, Class 1	Pass

Miscellaneous:

Application

Outdoor

Fogging (SAE J1756)

Pass

Mildew Resistance (ASTM G-21)

Pass

Finish

Clear Vinyl



OMNOVA Solutions Inc. • Fairlawn, OH 44333 • www.omnova.com
contact us at upholstery@omnova.com

BOLTASOFT is a registered trademark of OMNOVA Solutions Inc.
ALL OMNOVA PRODUCTS AND SERVICES ARE OFFERED AND SOLD SUBJECT TO THE OMNOVA
STANDARD TERMS AND CONDITIONS OF SALE AGREEMENT SET FORTH AT WWW.OMNOVA.COM
© 2010 OMNOVA Solutions Inc. 08/10
QA# 023-CP-076 • 04/21/05 • R:1