



Dynasty

**Product Specifications:**

**General**

|                                      |          |
|--------------------------------------|----------|
| Total Wt. - oz./sq. yd. (CFFA-700d)  | 20 ± 10% |
| Total Wt. - oz./lin. yd. (CFFA-700d) | 30       |
| Width (min.) - in. (CFFA-700a)       | 54"      |
| Face Content                         | PVC      |

**Backing**

|                      |            |
|----------------------|------------|
| Construction         | Terry Knit |
| Weight - oz./sq. yd. | 3.7        |
| Content              | Polyester  |
| Fiber Type           | Filament   |

**Adhesion (CFFA-3)**

|                      |                  |
|----------------------|------------------|
| Pounds/Inches (min.) | Warp 4<br>Fill 4 |
|----------------------|------------------|

**Tensile Strength (CFFA-17)**

|               |                    |
|---------------|--------------------|
| Pounds (min.) | Warp 85<br>Fill 75 |
|---------------|--------------------|

**Trap Tear Strength (CFFA-16c)**

|               |                    |
|---------------|--------------------|
| Pounds (min.) | Warp 20<br>Fill 27 |
|---------------|--------------------|

**Tack Strength (Stitch) (CFFA-14)**

|               |                    |
|---------------|--------------------|
| Pounds (min.) | Warp 35<br>Fill 30 |
|---------------|--------------------|

**Performance Testing:** meets or exceeds

**Abrasion (CFFA-1a)**

|                        |               |
|------------------------|---------------|
| Wyzenbeek, Wire Screen | 6,000 cycles  |
| Wyzenbeek, Cotton Duck | 10,000 cycles |

**Blocking (CFFA-4)**

No. 2 max

**W-Flex (CFFA-10)**

25,000 cycles

**Crock (CFFA-7)**

20 cycles - no stain

**UV (CFFA-2)**

|     |           |
|-----|-----------|
| QUV | 650 hours |
|-----|-----------|

**Cold Crack (CFFA-6a)**

|                    |       |
|--------------------|-------|
| Roller Temperature | -20°F |
|--------------------|-------|

**Flame Retardancy**

|                               |      |
|-------------------------------|------|
| FMVSS-302                     | Pass |
| California Tech. Bulletin 117 | Pass |
| BIFMA                         | Pass |
| UFAC Fabric, Class 1          | Pass |

**Miscellaneous:**

**Application**

Outdoor

**Fogging (SAE J1756)**

Pass

**Mildew Resistance (ASTM G-21)**

Pass

**Finish**

Clear Vinyl



OMNOVA Solutions Inc. • Fairlawn, OH 44333 • www.omnova.com  
contact us at upholstery@omnova.com

BOLTASOFT is a registered trademark of OMNOVA Solutions Inc.  
ALL OMNOVA PRODUCTS AND SERVICES ARE OFFERED AND SOLD SUBJECT TO THE OMNOVA  
STANDARD TERMS AND CONDITIONS OF SALE AGREEMENT SET FORTH AT WWW.OMNOVA.COM  
© 2010 OMNOVA Solutions Inc. 08/10  
QA# 023-CP-076 • 04/21/05 • R:1