

## Marlin Product Details

<b>Market:</b>	<a href="#">Automotive</a> <a href="#">Marine</a>
<b>Content:</b>	Vinyl Topcoat
<b>Backing:</b>	Polyester Hi-loft2TM
<b>Finishes and Treatments:</b>	Superior Abrasion - Martindale (EN ISO 12947:1999 Part 2) (>100.000 cycles) UV-Resistance XENOTEST DIN 54004/ NTC 1479 Cold Crack -23C Mildew Resistant Backing and Face Anti-stain Finish Permaguard
<b>Width:</b>	
<b>Roll Size:</b>	30 yd
<b>Flame Retardancy*:</b>	IMO A.652 (16) Annex I 8.2 & 8.3 EN 1021 Part 1 & 2 Directive 95/28/CE IMO A.652(16)Annex 1 8.2 and 8.3 (MED) Council Directive 96/98 EC on marine equipment FMVSS 302

\*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Our products, when tested with suitable component materials, may comply with California Technical Bulletin 133 and Boston Fire Code (test BFD IX-1).

Certain clothing and accessory dyes (such as those used on denim jeans) may migrate to lighter colors. This phenomenon is increased by humidity and temperature and is irreversible.

Spradling International, Inc. will not assume responsibility for dye transfer caused by external contaminants.