

NASSIMI

Nassimi LLC T 212.643.8080
370 Seventh Avenue T 800.521.5208
Suite 1600 F 212.643.2626
New York, NY 10001 W www.nassimi.com

Product Specification Sheet

Pattern: Beachcomber

Date: 06/13/2012

Team Performance

General Specifications

Weight (linear yard)	32 oz
Width	54 "
Thickness	1.0 mm
Surface Composition	PVC
Substrate Composition	100% Polyester
Substrate Weight	3.75 oz

General Treatments

UV Resistance CFFA-2 / ASTM G26-96 Method C	1,000 Hours
Cold Crack CFFA-6 Federal Standard No. 191A-Method 5874	-20 F
Mildew Resistant CFFA-120 / ASTM G21-96	Pass

Physical Strength Properties

Abrasion CFFA-1A/ Method ASTM D 4157-92	190,000+ Cycles
Tear Strength FTM 5136	25.8 Warp 27.7 Fill
Breaking Strength FTM 5100.1	89.2 Warp 102.7 Fill

Flame Retardancy Standards

California Technical Bulletin 117	Pass
UFAC Class I	Pass
BIFMA CS-191-53, Section 3	Pass
BIFMA Upholstery, Section 4	Pass
MVSS 302	Pass
NFPA 260	Pass
IMO A.652 (16) 8.2	Pass
IMO A.652 (16) 8.3	Pass

** CAL 133 (when used with suitable components)

*** Can be treated to pass FAR 25.853