Sprayway_®

SAFETY DATA SHEET

1. Identification

| Product number | 1000014030 |
|-----------------------------------|---|
| Product identifier | CHERRY TOTAL RELEASE BLAST OUT |
| Company information | Sprayway, Inc. 1005 S. Westgate Drive Addison, IL 60101 United States |
| Company phone | General Assistance 1-630-628-3000 |
| Emergency telephone US | 1-866-836-8855 |
| Emergency telephone outside US | 1-952-852-4646 |
| Version # | 01 |
| Recommended use | Air Freshener |
| Recommended restrictions | None known. |
| 2. Hazard(s) identification | |

| Physical hazards | Flammable aerosols | Category 1 |
|-----------------------|---|-----------------------------|
| Health hazards | Serious eye damage/eye irritation Category 2A | |
| | Specific target organ toxicity, single exposure | Category 3 narcotic effects |
| Environmental hazards | Not classified. | |
| OSHA defined hazards | Not classified. | |
| Label elements | | |



| | ▼ ▼ |
|--|---|
| Signal word | Danger |
| Hazard statement | Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness. |
| Precautionary statement | |
| Prevention | Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye/face protection. |
| Response | If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. |
| Storage | Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNOC) | None known. |
| Supplemental information | None. |
| | |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|---------------|--------------------------|------------|---------|
| Acetone | | 67-64-1 | 60 - 80 |
| Butane | | 106-97-8 | 10 - 20 |

| Chemical name | Common name and synonyms | CAS number | % |
|---------------------------------------|--------------------------|------------|----------|
| Propane | | 74-98-6 | 10 - 20 |
| Other components below reportable lev | els | | 2.5 - 10 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

| 4. First-aid measures | |
|--|--|
| Inhalation | If inhalation of gas/fume/vapor/dust/mist from the material is excessive (air concentration is greater than the TLV or health effects are noticed), immediately remove the affected person(s) to fresh air. Call a physician or Poison Control Center immediately. Call a POISON CENTER or doctor/physician if you feel unwell. |
| Skin contact | Wash off with soap and water. Get medical attention if irritation develops and persists. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately. |
| Ingestion | In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth thoroughly. |
| Most important symptoms/effects, acute and delayed | Irritation of eyes and mucous membranes. May cause drowsiness or dizziness. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Symptoms may be delayed. |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. |
| 5. Fire-fighting measures | |
| Suitable extinguishing media | Powder. Alcohol resistant foam. Water. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use a solid water stream as it may scatter and spread fire. |
| Specific hazards arising from the chemical | Contents under pressure. Pressurized container may explode when exposed to heat or flame. |
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection. |
| Fire-fighting equipment/instructions | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes. |
| General fire hazards | Extremely flammable aerosol. |
| 6. Accidental release meas | sures |
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For |

| | entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
|---|---|
| Methods and materials for containment and cleaning up | Refer to attached safety data sheets and/or instructions for use. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of low areas. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. This material and its container must be disposed of as hazardous waste. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

| Precautions for safe handling | Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear personal protective equipment. Observe good industrial hygiene practices. Wash thoroughly after handling. Do not empty into drains. |
|---|---|
| Conditions for safe storage, including any incompatibilities | Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 3 Aerosol. |
| 8. Exposure controls/perse | onal protection |

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Туре | 9 | Va | lue |
|---------------------------------|---|---|--------------------|---|
| Acetone (CAS 67-64-1) | PEL | | 24 | 00 mg/m3 |
| | | | 10 | 00 ppm |
| Propane (CAS 74-98-6) | PEL | | 18 | 00 mg/m3 |
| | | | 10 | 00 ppm |
| US. ACGIH Threshold Li | mit Values | | | |
| Components | Туре | • | Va | lue |
| Acetone (CAS 67-64-1) | STEL | - | 75 | 0 ppm |
| | TWA | | 50 | 0 ppm |
| Butane (CAS 106-97-8) | STEL | - | 10 | 00 ppm |
| US. NIOSH: Pocket Guid | le to Chemical Hazards | | | |
| Components | Туре | • | Va | lue |
| Acetone (CAS 67-64-1) | TWA | | 59 | 0 mg/m3 |
| | | | 25 | 0 ppm |
| Butane (CAS 106-97-8) | TWA | | 19 | 00 mg/m3 |
| | | | 80 | 0 ppm |
| Propane (CAS 74-98-6) | TWA | | 18 | 00 mg/m3 |
| | | | 10 | 00 ppm |
| logical limit values | | | | |
| ACGIH Biological Expos | ure Indices | | | |
| Components | Value | Determinant | Specimen | Sampling Time |
| Acetone (CAS 67-64-1) | 50 mg/l | Acetone | Urine | * |
| * - For sampling details, p | lease see the source doci | ument. | | |
| propriate engineering htrols | Ensure adequate ve | entilation, especial | ly in confined are | as. Provide eyewash station. |
| ividual protection measu | res, such as personal pr | otective equipm | ent | |
| Eye/face protection | | ection. Wear safet | | le shields (or goggles). Wear tight-fitting |
| Hand protection | Wear protective gloves. | | | |
| Skin protection | | | | |
| Other | Wear appropriate cl | hemical resistant of | lothing. | |
| Respiratory protection | | If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. | | |
| | Wear appropriate thermal protective clothing, when necessary. | | | |
| Thermal hazards | Wear appropriate th | iermal protective o | lothing, when ne | cessary. |

General hygiene
considerationsWhen using do not smoke. Do not get in eyes. Avoid contact with eyes. Avoid contact with skin.
Keep away from food and drink. Always observe good personal hygiene measures, such as
washing after handling the material and before eating, drinking, and/or smoking. Routinely wash
work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

| o. i nyolear ana chemiear p | noper neo |
|--|--|
| Appearance | Clear. |
| Physical state | Liquid. |
| Form | Aerosol. |
| Color | Colorless. |
| Odor | Not available. |
| Odor threshold | Not available. |
| рН | Not available. |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | Not available. |
| Flash point | -156.0 °F (-104.4 °C) Propellant estimated |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or exp | losive limits |
| Flammability limit - lower (%) | 1.9 % estimated |
| Flammability limit - upper (%) | 9.5 % estimated |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | 55 - 75 psig @ 70'F estimated |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Specific gravity | 0.714 estimated |
| 40 Otability and us activity | |

10. Stability and reactivity

| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
|---------------------------------------|---|
| Chemical stability | Risk of ignition. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Heat, flames and sparks. Avoid temperatures exceeding the flash point. |
| Incompatible materials | Strong oxidizing agents. Acids. Fluorine. Chlorine. Nitrates. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| Ingestion | Expected to be a low ingestion hazard. |
|--------------|--|
| Inhalation | Prolonged inhalation may be harmful. Narcotic effects. |
| Skin contact | Not available. |
| Eye contact | Causes serious eye irritation. |

Symptoms related to the physical, chemical and toxicological characteristics Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

| Acute toxicity | Narcotic effects. | |
|-------------------------------------|--|------------------------|
| Product | Species | Test Results |
| CHERRY TOTAL RELEASE BI | LAST OUT (CAS Mixture) | |
| Acute | | |
| Dermal | | |
| LD50 | Rat | 28569 mg/kg |
| Inhalation | | |
| LC50 | Rat | 104 mg/l/4h |
| Components | Species | Test Results |
| Acetone (CAS 67-64-1) | | |
| Acute | | |
| Dermal | | |
| LD50 | Guinea pig | > 7426 mg/kg, 24 Hours |
| | | > 9.4 ml/kg, 24 Hours |
| | Rabbit | > 7426 mg/kg, 24 Hours |
| | | > 9.4 ml/kg, 24 Hours |
| Inhalation | | |
| LC50 | Rat | 55700 ppm, 3 Hours |
| | | 132 mg/l, 3 Hours |
| | | 50.1 mg/l |
| Oral | | |
| LD50 | Rat | 5800 mg/kg |
| | | 2.2 ml/kg |
| Butane (CAS 106-97-8) | | |
| Acute | | |
| Inhalation | | |
| LC50 | Mouse | 1237 mg/l, 120 Minutes |
| | | 52 %, 120 Minutes |
| | Rat | 1355 mg/l |
| Propane (CAS 74-98-6) | | |
| Acute | | |
| Inhalation | | |
| LC50 | Mouse | 1237 mg/l, 120 Minutes |
| | | 52 %, 120 Minutes |
| | Rat | 1355 mg/l |
| | | 658 mg/l/4h |
| | | Ŭ |
| | y be based on additional component data not s | hown. |
| Skin corrosion/irritation | Not applicable. | |
| Serious eye damage/eye rritation | Causes serious eye irritation. | |
| Respiratory or skin sensitiza | tion | |
| Respiratory sensitization | Not available. | |
| Skin sensitization | This product is not expected to cause skin | sensitization. |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. | |
| | | |

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Carcinogenicity

| OSHA Specifically Regulate | d Substances (29 CFR 1910.1001-1050) |
|---|--|
| Not listed. | |
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. |
| Specific target organ toxicity - single exposure | Narcotic effects. |
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | Not likely, due to the form of the product. |
| Chronic effects | Prolonged inhalation may be harmful. Prolonged or repeated exposure may cause lung injury. |

12. Ecological information

Ecotoxicity

Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

| Product | | Species | Test Results |
|----------------------------|-----------------|--|----------------------------|
| CHERRY TOTAL RELEAS | SE BLAST OUT | (CAS Mixture) | |
| Aquatic | | | |
| Crustacea | EC50 | Daphnia | 19997 mg/L, 48 Hours |
| Fish | LC50 | Fish | 7914 mg/L, 96 Hours |
| Components | | Species | Test Results |
| Acetone (CAS 67-64-1) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 21.6 - 23.9 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 4740 - 6330 mg/l, 96 hours |
| * Estimates for product ma | y be based on | additional component data not shown. | |
| sistence and degradabilit | y No data is | No data is available on the degradability of this product. | |
| accumulative potential | No data a | No data available. | |
| Partition coefficient n-oc | tanol / water (| log Kow) | |
| Acetone | | -0.24 | |
| Butane | | 2.89 | |
| Propane | | 2.36 | |

| Mobility in soil | No data available. |
|-----------------------|---|
| Other adverse effects | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. |

13. Disposal considerations

| Disposal instructions | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. | | |
|---|---|--|--|
| Local disposal regulations | Dispose in accordance with all applicable regulations. | | |
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. | | |
| US RCRA Hazardous Waste U List: Reference | | | |
| Acetone (CAS 67-64-1) | U002 | | |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). | | |
| Contaminated packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers. | | |
| 14 Transport information | | | |

14. Transport information

| DOT |
|-----|
|-----|

| UN number | UN1950 |
|-----------|--------|
|-----------|--------|

| UN proper shipping name Transport hazard class(es) | Aerosols, flammable, (each not exceeding 1 L capacity) |
|---|---|
| Class | 2.1 |
| Subsidiary risk | - |
| Label(s) | 2.1 |
| Packing group | Not applicable. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. |
| Special provisions | N82 |
| Packaging exceptions | 306 |
| Packaging non bulk | None |
| Packaging bulk | None |

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

ΙΑΤΑ

| UN number | UN1950 |
|---|---|
| UN proper shipping name | Aerosols, flammable |
| Transport hazard class(es) | |
| Class | 2.1 |
| Subsidiary risk | - |
| Label(s) | 2.1 |
| Packing group | Not applicable. |
| Environmental hazards | Yes |
| ERG Code | 10L |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. |
| Other information | |
| Passenger and cargo aircraft | Allowed. |
| Cargo aircraft only | Allowed. |
| Packaging Exceptions | LTD QTY |
| IMDG | |
| UN number | UN1950 |
| UN proper shipping name | AEROSOLS |
| Transport hazard class(es) | |
| Class | 2.1 |
| Subsidiary risk | - |
| Label(s) | 2.1 |
| Packing group | Not applicable. |
| Environmental hazards | |
| Marine pollutant | Yes |
| EmS | F-D, S-U |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. |
| Packaging Exceptions | LTD QTY |
| Transport in bulk according to | Not applicable. |
| Annex II of MARPOL 73/78 and the IBC Code | |
| | |







IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) Acetone (CAS 67-64-1)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

Hazard categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated.

Acetone (CAS 67-64-1)

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number**

6532

6532

35 %WV

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1)

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)

US state regulations

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Rhode Island RTK

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | No |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | No |
| New Zealand | New Zealand Inventory | No |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| Issue date | 05-07-2015 |
|------------|------------|
| Version # | 01 |

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.