

NASSIMI

Nassimi LLC T 212.643.8080
370 Seventh Avenue T 800.521.5208
Suite 1600 F 212.643.2626
New York, NY 10001 W www.nassimi.com

Product Specification Sheet

Pattern: Classic

Date: 05/26/2011

THE SYMPHONY COLLECTION

General Specifications

Weight (linear yard)	29.0 oz
Width	54 "
Thickness	1.20 mm
Gauge	0.480
Emboss	Classic
Surface Composition	PVC
Substrate Composition	100% Polyester
Substrate Weight	4.4 oz

General Treatments

UV Resistance	1000 Hours	ASTM G154-06 & AATCC 16-2004, Option 3
Cold Crack	-20 F	CFFA-6 Federal Standard No. 191A-Method 5874
Mildew Resistant	Pass	CFFA-120 / ASTM G21-96
Anti-Bacterial	Pass	CFFA-300 / AATCC* Test Method 147-1998
Anti-Microbial	Pass	CFFA-300 / AATCC* Test Method 147-1998
Resilience SR	Yes	
Bleach Resistant	Yes	Diluted 1:10

Physical Strength Properties

Abrasion	500,000 Cycles	CFFA-1A / Method ASTM D 4157-10 ACT Standard Cottonduck
Tear Strength	7.9 Warp 7.7 Fill	CFFA-16 / ASTM D2261-07a
Breaking Strength	142 Warp 97 Fill	CFFA-17 / ASTM D751-06
Seam Strength Tack Tear	58 Warp 41 Fill	CFFA-14 / Method ASTM D751-06
Crocking	5 Dry 5 Wet	AATCC-Method 8-2007
Flex Testing of Finish	25,000 Warp 25,000 Fill	CFFA-10 / ASTM D2097-03(2005)
Coating Adhesion	12.1 Warp 9.8 Fill	ASTM D751-06

Flame Retardancy Standards

California Technical Bulletin 117, Section E	Pass	Boston Fire Code (BFD IX-1)	Pass
UFAC Class I	Pass	IMO A.652(16)8.2	Pass
BIFMA CS-191-53, Section 3	Pass	IMO A.652(16)8.3	Pass
BIFMA Upholstery, Section 4	Pass	ASTM E84 Adhered: Class I or A	Pass
MVSS 302	Pass	NY/NJ Port Authority	Pass
NFPA 260	Pass		