

WARRIOR - SPARTAN

**Applications- Healthcare, Casino, Cinema, Auto/RV,
Marine, Hospitality, Fitness, Corporate & Residential**

TECHNICAL DATA SHEET

Pattern Name	WARRIOR SPARTAN
Finish	FORBID _{SRT}
Composition	PVC Expanded
Weight (± 2.5 oz /lin yd)	36 oz
Thickness (± 10% mm)	1.35 mm
Backing	100% Polyester
Backing Weight	6.2 oz
Width (-0/+1 in)	54 in
Roll Put Up (yds)	30 yds



Flame Retardancy	Meets AB2998
Contains No Flame Retardants	
CA TB117:2013	BIFMA Class A
UFAC Class 1	NFPA 260: 2019 Class 1

May comply with the above when tested with suitable components. These indicate typical performance and do not imply material behavior under actual fire conditions.

Class Rating	
Grade A / Class A	ASTM D3690
Anti-Mildew: Pass	ASTM G21
Anti-Bacterial: Pass	AATCC 147
Anti-Pinking: Pass	ASTM E1428

PERFORMANCE STANDARDS

Surface Abrasion	CFFA-1 Wyzenbeek
1,800,000+ DR	Pass
UV Stability	ASTM D4329
QUV Exposure 650 hrs	Grey Scale 3.5 Min.
Cold Crack	FED 191A-5874
-10°F / -23.33°C	

Croaking Resistance	CFFA-7
Dry: 4 Min. Excellent	Wet: 3 Min. Good
Blocking Resistance	CFFA-4
No Blocking	
Coating Adhesion	CFFA-3
MD 4.5 LBS Min.	CD 3.5 LBS Min.

Breaking Strength	ASTM D751:06
Cut Strip Test Method	
MD 90 LBS Min.	CD 60 LBS Min.

Tearing Strength	CFFA-16B
Tongue Tear Method	
MD and CD	8 LBS Min.

Information contained herein are typical values based on standard performance testing, and while believed to be accurate, is subject to change and variation. This information does not imply warranty or fitness for a particular purpose; users are responsible for determining whether the product is suitable for their method of use and application and are recommended to evaluate the material for their specific requirements.

Rex Pegg Fabrics, Inc
1802 East Stewart Street
Tacoma WA 98421
Toll Free (800) 933-3232
Email
sales@rexpeggfabrics.com



Phoenix Trim & Supply
2359 N 33rd Ave
Phoenix AZ 85009
Toll Free (800) 369-5084
Email
azsales@rexpeggfabrics.com